

CHOIX MATIERES

	PMMA Coulé	PMMA Extrudé	PET/PETG	PC Standard	PC UV	PC Anti-reflet	PC Anti-abrasion
Incolore	☺	☺	☺	☺	☺	☺	☺
Diffusant	☺	☺	☺	☺	☺	☺	
Opaque	☺						
Couleur	☺	☺	☺	☺	☺	☺	☺
Brillant	☺	☺	☺	☺	☺		☺
Mat	☺	☺				☺	
Lisse	☺	☺	☺	☺	☺	☺	☺
Texturé	☺				☺		
Densité	1.19	1.19	1.33	1.2	1.2	1.2	1.2
T° d'utilisation en °C	-20 / + 80	-20 / + 80	-40 / +60	-40 / +130	-40 / +130	-40 / +130	-40 / +120
Classement feu/fumée			M2				
Résistance							
Aux UV	+	+	+	=	+	+	+
Au choc	=	=	+	+	+	+	+
Chimique	=	=	+	-	-	-	+
A l'abrasion	=	=	=	=	=	=	+
Mise en œuvre							
Impression	+	+	+	+	+	+	-
Thermoformage	+	+	+	+	+	+	-
Pliage à froid	-	-	+	+	+	+	-
Pliage à chaud	+	+	+	+	+	+	-
Collage	+	=	-	=	=	=	-
Soudage	=	-	+	+	+	+	-
Budget	@ @	@	@ @	@ @	@ @ @	@ @ @	@ @ @

☺ oui

+ performant

= sous conditions

- peu ou pas recommandé